

MATERIAL SAFETY DATA SHEET

KOP-COAT, INC
MARINE GROUP EAST
36 PINE STREET
ROCKAWAY
NJ 07866

EMERGENCIES
HEALTH/SPILLS.....: 800-548-0489
CHEMTREC ASSISTANCE: 800-424-9300
CHEMTREC OUTSIDE US: 703-527-3887
CANUTEC.....: 613-996-6666

KOP-COAT, INC
PRODUCT INFORMATION: 800-221-4466
OUTSIDE USA.....: 973-625-3100

1 PRODUCT IDENTIFICATION

PRODUCT NAME: 3229 Easyoxy Bikini Blue
PRODUCT USE: Topside coating
APPEARANCE: Blue liquid with hydrocarbon odor
CAS NUMBER: Mixture
SYNONYMS: None

REVISION...: 4
DATE.....: 1/06/00
MSDS NUMBER: 1322900

2 HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENT	REG AGENCY	PPM	NOTES	MG/M3	NOTES
Calcium carbonate (Limestone) CAS NUMBER:1317-65-3 PERCENT BY WGT: 5 TO 10	ACGIH-TWA	-		10	1
	OSHA TWA	-		15	1
	OSHA-TWA	-		5	2
Titanium dioxide CAS NUMBER:13463-67-7 PERCENT BY WGT: 10 TO 15	ACGIH-TWA	-		10	
	NIOSH	-	(+)	-	(+)
	OSHA TWA	-		10	1
Mineral spirits CAS NUMBER:64742-47-8 PERCENT BY WGT: 5 TO 10	ACGIH TWA	100		525	
	NIOSH	-		350	
	NIOSH STEL	-		1800	4
	OSHA TWA	100		525	
Petroleum naphtha CAS NUMBER:64742-88-7 PERCENT BY WGT: 5 TO 10	NIOSH	-		350	
	NIOSH STEL	-		1800	4
	OSHA TWA	400		1600	
Mineral spirits CAS NUMBER:8052-41-3 PERCENT BY WGT: 15 TO 20	ACGIH TWA	100		-	
	NIOSH	-		350	
	OSHA TWA	100		-	

NOTES:
1) Total dust
2) Respirable fraction
4) The short term exposure limit (STEL) is a 15-minute TWA that should not be exceeded at any time during a workday.
(+) NIOSH Occupational Carcinogen

3 HAZARDS IDENTIFICATION

EYE: Direct contact with liquid or vapor causes irritation.

SKIN: Prolonged or repeated contact with the skin can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION: Avoid breathing vapors or mists. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches). Prolonged or repeated inhalation and ingestion may cause delayed injury involving the kidneys and the blood.

PRODUCT NAME: 3229 Easypoxy Bikini Blue

PAGE 2 OF 4

3 HAZARDS IDENTIFICATION

INGESTION: Irritating to the nose, throat and respiratory tract. May cause vomiting. Aspiration of this product into the lung may cause chemical pneumonitis which can be fatal.

Individuals with pre-existing disease in or a history of ailments involving the skin, eye, respiratory tract, liver, kidney, central nervous system are at a greater than normal risk of developing adverse effects when exposed to this material.

4 FIRST AID MEASURES

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash thoroughly with soap and water. If redness, itching, burning or other symptoms develop or persist, get medical attention. Wash contaminated clothing before reuse.

INHALATION: If you experience difficulty in breathing, leave the area to obtain fresh air. If breathing has stopped have a trained person administer artificial respiration preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

INGESTION: If swallowed do NOT induce vomiting. Get immediate medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

NOTE TO PHYSICIAN: There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

5 FIRE FIGHTING MEASURES

FLASH POINT: 109 F/44C

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, water spray or foam.

FIRE FIGHTING PROCEDURES: As in any fire, wear complete fire service protective equipment, including full-face MSHA/NIOSH approved or equivalent self-contained breathing apparatus. Use water to cool fire-exposed container/structure/protect personnel.

FIRE AND EXPLOSION HAZARDS: Can release vapors that form explosive mixtures. Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat (fire). Toxic vapors may be given off in a fire.

6 SPILL AND LEAK PROCEDURES

Stop spill/leak if no risk involved. Avoid breathing vapors. Use an inert absorbent to complete a clean-up. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7 HANDLING AND STORAGE

HANDLING: Avoid prolonged or repeated breathing of vapors, mists or fumes. Do not get on skin, in eyes or on clothing. Wash thoroughly after handling.

STORAGE: Keep in a closed, labeled container within a cool (well-shaded), dry, ventilated area. Protect from physical damage. Keep containers closed when material is not in use. Maintain good housekeeping.

PRODUCT NAME: 3229 Easyoxy Bikini Blue

PAGE 3 OF 4

7 HANDLING AND STORAGE

OTHER: Keep away from heat and open flame. Do not use until manufacturer's precautions have been read/understood.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Facilities storing or utilizing this product should be equipped with an eyewash facility.

RESPIRATORS: Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. A respiratory protection program that meets OSHA 1910.134 and NIOSH 42 CFR 84 requirements must be followed whenever workplace conditions warrant a respirator's use.

PERSONAL PROTECTIVE EQUIPMENT: Industrial safety glasses at a minimum. As necessary for work area conditions: use side shields, goggles, or faceshield. As required, chemical resistant flexible-type gloves (heavy duty neoprene or equal). Wear industrial-type work clothing and safety footwear. Depending on working conditions, i.e., contact potential, wear resistant protective garments such as head/neck cover, aprons, jackets, pants, coveralls, boots, etc.

9 PHYSICAL AND CHEMICAL PROPERTIES

Weight Per Gallon (lbs):	9.170	% VOL by Weight.:	Not determined
Vapor Density.:	(Air=1)>1	Boiling Point.:	Not determined
Vapor Pressure:	Not determined	Evaporation Rate: (ether=1)<1	
pH.:	Not determined	Specific Gravity:	> 1
Solubility in Water:	Negligible	Viscosity.:	Not determined
VOC Content.:	380 g/L		

10 STABILITY AND REACTIVITY DATA

STABILITY: None
HAZARDOUS POLYMERIZATION: None
INCOMPATIBILITY: Avoid oxidizing agents, heat, sparks and open flames.
HAZARDOUS DECOMPOSITION PRODUCT(S): Carbon monoxide, carbon dioxide upon thermal decomposition.

11 TOXICOLOGICAL INFORMATION

Contact Kop-Coat for applicable information.

12 ECOLOGICAL INFORMATION

Product has not been tested for ecotoxicity.

13 DISPOSAL CONSIDERATIONS

This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state and federal regulations.

14 TRANSPORTATION INFORMATION

PRODUCT NAME: 3229 Easyoxy Bikini Blue

PAGE 4 OF 4

14 TRANSPORTATION INFORMATION

DEPARTMENT OF TRANSPORTATION REPORTABLE QUANTITIES REPORTABLE QTY (LBS)	HAZARDOUS SUBSTANCE
100	Xylene

DOT PROPER SHIPPING NAME: None
 DOT HAZARD CLASS: None
 LABEL: Non-Hazardous
 DOT IDENTIFICATION NUMBER: None
 DOT information for domestic ground transportation.

15 REGULATORY INFORMATION

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

No information available.

16 OTHER INFORMATION

NOTICE: While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Kop-Coat, Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.

PREPARED BY: L. Briggs Manager Environmental and Regulatory Affairs