

**ROYSTON LABORATORIES DIVISION
CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

Computer Code: A-51 PLUS Mastic.doc

Date Prepared: February 27, 2004

SECTION I

PRODUCT NAME: Roskote A-51 Plus Mastic
CLASS: Resin/Bitumen Mastic
MANUFACTURER: Royston Laboratories Division
 Chase Corporation
TELEPHONE NO: (412) 828-1500
ADDRESS: 128 First Street
 Pittsburgh, PA 15238
EMERGENCY ONLY To be used only in the event of
TEL.#: 800-424-9300 chemical emergencies involving
OUTSIDE USA: a spill, leak, fire, exposure, or
703-527-3887 accident involving chemicals.

NFPA 704 HAZARD RATING		HEALTH
4 = Extreme		2
3 = High		
2 = Moderate		FIRE
1 = Slight		3
0 = Minimal		
* = Chronic Health Hazard (see Sect. V)		REACTIVITY
		1

NA = Not Applicable
 NE = Not Established
 UN = Unavailable

SECTION II - HAZARDOUS INGREDIENTS	%	TLV	PEL	CAS #
Toluene	30 - 40	100 ppm (TWA)	100 ppm (TWA) 150 ppm (STEL)	108-88-3
Methyl Ethyl Ketone	< 5	200 ppm (TWA) 300 ppm (STEL)	200 ppm (TWA) 300 ppm (STEL)	78-93-3
Coal Tar Pitch*	40 - 45	0.2 mg/M ³	0.2 mg/M ³	65996-93-2
Coal Tar Pitch*	< 5	NE	NE	65996-90-9
Epoxy Resin	< 5	NE	NE	25036-25-3
Mica**	5 - 10	3 mg/M ³	3 mg/M ³	12001-26-2/ 1318-94-1
Talc**	< 5	UN	2 mg/M ³	14807-96-6

* Listed as a known carcinogen by NTP and/or IARC.

** Respirable dust.

SECTION III - PHYSICAL DATA

BOILING POINT (°F.):	174 - 232° F (78-110° C)	SPECIFIC GRAVITY (H ₂ O = 1):	1.107
VAPOR PRESSURE (MM Hg):	83 mm Hg @ 68° F (M.E.K.)	PERCENT VOLATILE BY VOLUME (%):	49%
VAPOR DENSITY (AIR = 1):	3.2 (Toluene)	pH:	NA
SOLUBILITY IN WATER:	Nil	EVAPORATION RATE (BuAc=1):	6.0 (M.E.K.)
APPEARANCE AND ODOR:	Black liquid. Aromatic hydrocarbon odor.		

INHALATION: Move to an area free from risk of further exposure. Treat symptomatically. Administer oxygen or artificial respiration as needed. **SEEK MEDICAL ATTENTION.**

SECTION VI - REACTIVITY DATA

STABILITY: Normally stable. Hazardous polymerization will not occur. Material is slightly combustible and should be stored away from excess heat and flames.

INCOMPATIBILITY: Strong oxidizers, concentrated Nitric and Sulfuric Acids and Halogens.

HAZARDOUS DECOMPOSITION PRODUCTS: Will produce fumes, smoke, carbon monoxide, carbon dioxide, and a variety of complex hydrocarbons during combustion.

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES: Eliminate all ignition sources (flares, flames, including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from the area of spill until clean up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid into salvage tank. Remaining material is to be taken up on sand, clay, earth, floor absorbent or other absorbent material and shoveled into containers.

WASTE DISPOSAL METHOD: Dispose of material in accordance with federal, state and local regulations. Before attempting clean up, refer to hazardous information listed on this sheet.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY: Avoid breathing of vapor or spray mist. Use an OSHA/NIOSH approved respirator as required to prevent overexposure. In accord with 29 CFR 1910.134, use either atmosphere supplied respirator or an air purifying respirator for organic vapors.

EYEWEAR: Wear safety glasses or goggles to prevent eye contact.

CLOTHING/GLOVES: Wear gloves or other protective clothing as required to minimize skin contact.

VENTILATION: Provide local exhaust ventilation in volume and pattern to keep TLV of all hazardous ingredients below acceptable limit. (Use of explosion proof ventilation as required to control vapor concentrations.)

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Keep away from heat, sparks and open flame. Keep containers closed when not in use. Use of adequate ventilation. Avoid prolonged or repeated inhalation of vapor and skin contact. Store in accordance with NFPA, state and local regulations.

This product contains Coal Tar Pitch. The IARC monographs (Volume 35) state that there is sufficient evidence that Coal Tar Pitches are carcinogenic in humans and that there is sufficient evidence that occupational exposure to Coal Tars as it occurs during the destructive distillation of coal is causally associated with the occurrence of skin cancers in humans. It is also listed in the NTP and in OSHA Sub-part Z Table.

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372:

<u>CAS #</u>	<u>CHEMICAL NAME</u>	<u>PERCENT BY WEIGHT</u>
108-88-3	Toluene	30 - 40
78-93-3	Methyl Ethyl Ketone	< 5

This information must be included in all MSDS that are copied and distributed for this material.

Legal responsibility is assumed only for the fact that all studies reported here and all opinions are those of qualified experts.

FFF:cls
02/27/04
A-51 PLUS MASTIC.doc