

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards

HMIS: HAZARD RATINGS

HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
PHYSICAL HAZARD	0	2 = MODERATE	



TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Not Regulated	REF:	Not Applicable
HAZARD CLASS / PKG GRP:	Not regulated	LABEL:	None Required
IDENTIFICATION NUMBER:	None		

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

CP Weld Metal

Page 1 of 2

MANUFACTURER'S NAME

Thermoweld

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

ADDRESS (NUMBER, STREET, P.O. BOX)

4102 South 74th East Ave.

TELEPHONE NUMBER FOR INFORMATION

(800) 558-1373

(CITY, STATE AND ZIP CODE)

Tulsa, OK 74145

DATE PREPARED: November 22, 2004

SUPERSEDES: May 28, 2003

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS

(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))

CAS #

% (OPTIONAL)

OSHA PEL

ACGIH TWA

SARA

RQ

PPM

MG/M3

PPM

MG/M3

TITLE III

LBS

Cuprous oxide (a)

1317-39-1

60 - 90

1

Yes

Copper (a,b)

7440-50-8

7 - 13

1.0

Yes

5000

Aluminum (fume or dust) (a)

7429-90-5

7 - 13

15

10

Yes

(a) A "Yes" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

(b) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, if < 4 μ diameter, according to 40 CFR 302.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE

INHALATION: Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract. Contains substances which are considered nuisance dusts which require a NIOSH approved respirator when airborne particulate exceeds maximum allowable limit.

SKIN: None expected, however, prolonged contact may cause irritation.

EYES: Contact with eyes may cause irritation.

INGESTION: May cause gastric distress, stomach pains, vomiting and diarrhea.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

EMERGENCY AND FIRST AID PROCEDURES

Remove affected person to fresh air; if symptoms persist seek medical attention.

Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Give two glasses of water for dilution; induce vomiting as directed by medical personnel; never give anything by mouth to an unconscious person; seek medical attention.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)
CP Weld Metal

Page 2 of 2
Date: November 22, 2004

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Not applicable	NFPA RATING None	FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable
---	---------------------	---

EXTINGUISHING MEDIA
Use dry sand, graphite, dolomite, sodium chloride, water spray or chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES
Firefighters must wear full facepiece self-contained breathing apparatus in positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Thermoweld copper base welding/joining materials are exothermic mixtures, which when reacted, produce hot molten materials with temperatures in excess of 4000° F and a localized release of smoke. The materials are not explosive, ignition temperatures are in excess of 850° F for starting material and 1750° F for base material. They are not shock sensitive, nor are they subject to spontaneous ignition. Should the material be accidentally ignited, the immediate and direct application of large volumes of water will effectively retard the spread of fire and control it. Large amounts of dense, dusty smoke will be liberated during an accidental fire.

SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Confine and segregate product for reuse; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424-8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Storage of Thermoweld Exothermic materials should be in a clean dry area and restricted to access by authorized personnel only. Do not subject to rough handling or physical damage, nor excessive vibration. Store in accordance with "This Side Up" labels. Protect from weather and moisture. DO NOT USE PRODUCTS THAT HAVE BEEN EXPOSED TO MOISTURE. Before using Thermoweld Exothermic Process, personnel should be trained by a Thermoweld representative. Read and understand the instruction sheet packaged with the mold, and observe all general and safety instructions.

SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): NIOSH approved respirator designed to remove airborne particulate present in excess of maximum allowable concentrations due to secondary operations such as mixing, spraying, sanding, buffing, etc. Refer to 29 CFR 1910.134 or European Standard EN 149 for regulations.

VENTILATION	LOCAL EXHAUST: Recommended MECHANICAL (GENERAL): Yes	SPECIAL: None OTHER: None
PROTECTIVE GLOVES: Neoprene or rubber gloves.	EYE PROTECTION: Protective eyeglasses or chemical safety goggles.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash nearby		

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT Not applicable	SPECIFIC GRAVITY (WATER = 1) Approximately 6.0
VAPOR PRESSURE (MM Hg) Not applicable	pH Not applicable
VAPOR DENSITY (AIR = 1) Not applicable	EVAPORATION RATE (WATER = 1) Not applicable
SOLUBILITY IN WATER Insoluble	% VOLATILE (BY WEIGHT) None
APPEARANCE AND ODOR Gray / silver granules, characteristic odor	

SECTION 9 - STABILITY AND REACTIVITY

STABILITY	UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Avoid generating airborne dust
-----------	--------------------------	---

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of fire, smoke, oxides of carbon, fumes of copper and aluminum. Small amounts of fluoride fume or hydrofluoric fume may be released under ignition.

HAZARDOUS POLYMERIZATION	MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None
--------------------------	-----------------------------------	---------------------------

SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Do not flush to sanitary sewer or waterway. Refer to 40 CFR Protection of Environment Parts 260 - 299 for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable, and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendor or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.