

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

Product: Roskote R 28 Rubberized Mastic™

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: ROYSTON DIVISION OF CHASE CORP.
128 FIRST STREET
PITTSBURGH, PA 15238

TELEPHONE INFORMATION: (412) 828-1500

EMERGENCY, CHEMTREC: 800-424-9300, Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: (703) 527-3887

REVISION DATE: April 10, 2007
PREPARED BY: Frederick F. Fischer, Jr.

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.
64742-04-7	Aromatic Oil	< 5
8052-42-4	Asphalt	35-45
12001-26-2	Mica*	5-10
14807-96-6	Talc*	10-20
108-88-3	Toluene	25-35

* Respiratory dust

3. HAZARDOUS IDENTIFICATION

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

INHALATION: Causes irritation of nasal passages and throat. Causes stupor (central nervous system depression).

SKIN CONTACT: Can cause moderate skin injury (reddening and swelling).

EYE CONTACT: Liquid and vapors are irritating to eyes. Can cause severe injury.

INGESTION: Can cause mental sluggishness.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

ACUTE: Can Cause severe eye irritation, redness, tearing, and blurred vision. Excessive inhalation of vapors can cause nausea, respiratory irritation, central nervous system effects, including dizziness, weakness, fatigue, nausea, headache, and possible unconsciousness and even death. Swallowing can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis, which is fatal.

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

CHRONIC: Prolonged and repeated skin contact can cause moderate irritation, defatting and dermatitis. Overexposure in laboratory animals has been found the cause of the following effects: Liver abnormalities, kidney damage, lung damage, and spleen damage. Overexposure to this material has been suggested as a cause for liver abnormalities in humans. Prolonged or repeated contact may lead to dermatitis, and with poor hygiene practices, to skin cancer. An Ingredient in this material has been listed as a carcinogen by IARC, NPT, QSHA, and ACGIH.

4. FIRST AID MEASURES

GENERAL ADVICE: Consult Physician immediately.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Move to an area free from risk of further exposure. Treat symptomatically. Administer oxygen or artificial respiration as needed. **SEEK MEDICAL ATTENTION.**

SKIN CONTACT: Repeated or prolonged contact can cause drying of skin and dermatitis. Remove contaminated clothing and launder thoroughly before reuse. Wash affected skin thoroughly with soap and water. **DO NOT USE SOLVENTS** on skin as they may promote absorption of this material. For severe exposure, get under safety shower after removing clothing, and then **SEEK MEDICAL ATTENTION** if irritation develops or persists after the area has been washed.

EYE CONTACT: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. Refer individual to a physician or ophthalmologist for immediate follow up. **SEEK MEDICAL ATTENTION.**

INGESTION: **DO NOT INDUCE VOMITING.** Give 1-2 cups of milk or water to drink. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION.**

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon Dioxide or dry chemical. Use self-contained breathing apparatus if applicable.

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Stable.

SENSITIVITY TO STATIC DISCHARGE: Expected to be sensitive to static discharge when vapors are present between the lower and upper explosive limits.

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS FOR PERSONNEL: Wear protective clothing. Use self-contained breathing apparatus if required.

ENVIRONMENTAL PRECAUTIONS: Avoid discharge to drains, sewers and natural water supply.

PROCESS FOR CLEANING: Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

7. HANDLING AND STORAGE

HANDLING: Ventilate work area sufficiently. Keep containers closed. Avoid contact with eyes, skin and clothing.

STORAGE: Store between -15°C and +35°C for solvent based coatings and thinners. Ground all metal containers. 55-gallon drums may be stored on their sides in a cradle designed for this purpose.

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION

MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION:

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.	NIOSH REL		VALUE	UNIT
			TWA	REL		
64742-04-7	Aromatic Oil	< 5	TWA	0.2	0.2	mg/m ³
8052-42-4	Asphalt	35-45	TWA	0.5	0.5	mg/m ³
12001-26-2	Mica	5-10	TWA	3.0	3.0	mg/m ³
14807-96-6	Talc	10-20	TWA	2.0	2.0	mg/m ³
108-88-3	Toluene	25-35	TWA	50	50	ppm

ADDITIONAL ADVICE: Use personal protective equipment, i.e., suitable work clothing, eye goggles and protective gloves. If spraying utilize protective facemask.

9. PHYSICAL PROPERTIES

ODOR: AROMATIC

CHANGE OF STATE	VALUE/AREA	UNIT	METHOD
FREEZING POINT:	N/A	°C	
BOILING POINT:	109-111 (229-232)	°C (°F)	
FLASH POINT:	7.2 (45)	°C (°F)	TCC
IGNITION TEMPERATURE:			
SPECIFIC GRAVITY:	1.247	H ₂ O = 1	
% VOLATILE BY VOLUME:	30-45	%	
SOLUBILITY IN WATER:	NEGLIGIBLE		
PH VALUE:	N/A		
VISCOSITY:		CPS	
FLAMMABLE LIMITS:	LEL 1.4 UEL 7.4		
EVAPORATION RATE:	2.4	BUAC = 1	

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Sparks and Open Flame.
MATERIALS TO AVOID: Contact with strong oxidizing, acidic or alkaline agents.
DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.
EYES: Splashes or spray vapors may cause irritation.
SKIN: Substance may be an irritant for sensitive skin.
INHALATION: May cause mild nausea/dizziness in some people when used in confined/unventilated areas. Move patient to fresh air. Give nothing by mouth.
CONSUMPTION: If accidentally swallowed may cause discomfort and requires plenty of water or milk to dilute. Do not induce vomiting. Seek medical assistance.

11. TOXICOLOGICAL INFORMATION

CAS NUMBER	IDENTIFICATION	DERMAL LD50	INHALATION LC50	ORAL LD50
64742-04-7	Aromatic Oil	N/E	N/E	N/E
8052-42-4	Asphalt	N/E	N/E	N/E
12001-26-2	Mica	N/E	N/E	N/E
14807-96-6	Talc	N/E	N/E	N/E
108-88-3	Toluene	12.3 g/kg (Rabbit)	4959 ppm (Rat)	7.0 g/kg (Rat)

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

CAS NUMBER	IDENTIFICATION	CARCINOGENICITY		TERATOGENICITY	MUTAGENICITY
		ACGIH	IARC		
64742-04-7	Aromatic Oil	N/E	Yes	N/E	N/E
8052-42-4	Asphalt	N/E	N/E	N/E	N/E
12001-26-2	Mica	N/E	N/E	N/E	N/E
14807-96-6	Talc	N/E	N/E	N/E	N/E
108-88-3	Toluene	N/E	N/E	Yes	N/E

12. ECOLOGICAL INFORMATION

VOLATILE ORGANIC COMPOUNDS: 330 Grams Per Liter (g/l), 2.75 Pounds Per Gallon (lb/g)

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

SHIPPING CLASS: UN1263 PAINT FLAMMABLE LIQUID; PACKING GROUP II

15. REGULATORY INFORMATION

SARA SECTION 302:
SARA (311,312) HAZARD CLASS:
SARA (313) CHEMICALS: TOLUENE
CERCLA: Toluene: 1000 LBS.
CPSC CLASSIFICATION:
HMIS: FLAMMABILITY: 3 REACTIVITY: 0 HEALTH: 2
NFPA: FLAMMABILITY: 3 REACTIVITY: 0 HEALTH: 2

CALIFORNIA PROPOSITION 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
- B. This product contains a chemical known to the State of CA to cause cancer.
- C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.

16. OTHER INFORMATION

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND ARE NOT A PRODUCT SPECIFICATION NOR WARRANTY, EITHER EXPRESSED OR IMPLIED IS MADE. THE STATED RECOMMENDED HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE.

C = Ceiling Limit, NEGL = Negligible, N/A = Not Applicable, N/E = Not Established, PROP = Proprietary.

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

Product: Royston Greenline Tape

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: ROYSTON DIVISION OF CHASE CORP.
128 FIRST STREET
PITTSBURGH, PA 15238

TEL INFORMATION: (412) 828-1500

ENCY, CHEMTREC: 800-424-9300. Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: (703) 527-3887

REVISION DATE: January 17, 2007
PREPARED BY: Frederick F. Fischer, Jr.

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.
1333-86-4	Carbon Black	5

3. HAZARDOUS IDENTIFICATION

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

INHALATION: Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat.

SKIN CONTACT: Normally not irritating. If rash develops or irritation persists, seek physician.

EYE CONTACT: If eye contact is made and irritation develops, contact physician.

INGESTION: Due to nature of product ingestion is not likely. If ingested, see physician.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

ACCUTE: Inhalation - exposure during hot process may cause respiratory. Eye or nose irritation.

CHRONIC: Inhalation - Long term exposure to concentrated hot processing fumes may reduce lung function and cause chronic bronchitis.

4. FIRST AID MEASURES

GENERAL ADVICE:

INHALATION: Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat. If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, **GET MEDICAL ATTENTION.**

SKIN CONTACT: Normally not irritating. If rash develops or irritation persists, seek physician.

EYE CONTACT: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, **GET MEDICAL ATTENTION.**

INGESTION: Due to nature of product ingestion is not likely. If ingested, see physician.

LO55 Rev. 03/30/06

Royston Greenline Tape

Page 1 of 4

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.

EYES: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, **GET MEDICAL ATTENTION.**

SKIN: If solid product gets on the skin, wash the contaminated skin with soap and water. If irritation develops or persists after the area has been washed.

INHALATION: If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, **GET MEDICAL ATTENTION.**

CONSUMPTION: If swallowed, call physician immediately. Only induce vomiting at the instructions of a physician. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.**

11. TOXICOLOGICAL INFORMATION

CAS NUMBER	IDENTIFICATION	DERMAL LD50	INHALATION LC50	ORAL LD50
1333-86-4	Carbon Black	N/E	27,000 mg/M ³ Rat Inhalation	> 8,000 mg/Kg Rat Ingestion

CAS NUMBER	IDENTIFICATION	CARCINOGENICITY ACGIH IARC	TERATOGENICITY	MUTAGENICITY
1333-86-4	Carbon Black	Yes Yes 2B	Yes	N/E

12. ECOLOGICAL INFORMATION

VOLATILE ORGANIC COMPOUNDS: 0 Grams Per Liter (g/l), 0 Pounds Per Gallon (lb/g).

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

SHIPPING CLASS: Not Regulated

15. REGULATORY INFORMATION

SARA SECTION 302:
SARA (311,312) HAZARD CLASS:
SARA (313) CHEMICALS: NONE
CERCLA: N/A
CPSC CLASSIFICATION:
HMIS: FLAMMABILITY: 0 REACTIVITY: 0 HEALTH: 1
NFPA: FLAMMABILITY: 0 REACTIVITY: 0 HEALTH: 1

CA - Proposition 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
 B. This product contains a chemical known to the State of CA to cause cancer.
 C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.

LO55 Rev. 03/30/06

Royston Greenline Tape

Page 3 of 4

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

SUITABLE EXTINGUISHING MEDIA: 5. FIRE FIGHTING MEASURES
Foam, Carbon Dioxide or dry chemical. If entering a confined area, use self-contained breathing apparatus if applicable.

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Stable

SENSITIVITY TO STATIC DISCHARGE: Stable

PRECAUTIONS FOR PERSONNEL: 6. ACCIDENTAL RELEASE MEASURES
No special clothes are required, but do wear gloves.

ENVIRONMENTAL PRECAUTIONS: No special procedures normally needed.

PROCESS FOR CLEANING: Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

7. HANDLING AND STORAGE

HANDLING: Avoid direct contact with product. No special ventilation required.

STORAGE: Store away from ignition sources and open flames.

8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION
MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION:

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.	NIOSH REL	VALUE	UNIT
1333-86-4	Carbon Black	< 5	TWA	50	ppm

ADDITIONAL ADVICE: No special clothes are required, but do wear gloves.

9. PHYSICAL PROPERTIES

ODOR: AROMATIC

CHANGE OF STATE	VALUE/AREA	UNIT	METHOD
FREEZING POINT:	N/A	°C	
BOILING POINT:	N/A	°C (°F)	
FLASH POINT:	N/A	°C (°F)	TCC
IGNITION TEMPERATURE:			
SPECIFIC GRAVITY:	1.4	H ₂ O = 1	
% VOLATILE BY VOLUME:	Nil	%	
SOLUBILITY IN WATER:	Insoluble		
PH VALUE:	N/A		
VISCOSITY:		CPS	
FLAMMABLE LIMITS:	LEL N/A UEL N/A		
EVAPORATION RATE:	N/A	BUAC = 1	

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Open Flame
MATERIALS TO AVOID: None known

LO55 Rev. 03/30/06

Royston Greenline Tape

Page 2 of 4

**ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET**

16. OTHER INFORMATION

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND ARE NOT A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED IS MADE. THE STATED RECOMMENDED HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE.

C = Ceiling Limit, NEGL = Negligible, N/A = Not Applicable, N/E = Not Established, PROP. = Proprietary.

LO55 Rev. 03/30/06

Royston Greenline Tape

Page 4 of 4

ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

Product: Roybond 747 Adhesive Aerosol

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED BY: ROYSTON DIVISION OF CHASE CORP.
128 FIRST STREET
PITTSBURGH, PA 15238

GENERAL INFORMATION: (412) 828-1500

EMERGENCY, CHEMTREC: 800-424-9300, Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: (703) 527-3887

REVISION DATE: April 12, 2007
PREPARED BY: Frederick F. Fischer, Jr.

2. COMPOSITION/INFORMATION ON INGREDIENTS

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.
108-88-3	Toluene	10-15
78-93-3	Methyl Ethyl Ketone	< 5
999-93-3	Hexamethyldisilazane	< 0.5
65996-93-2	Coal Tar Pitch*	< 5
67-64-1	Acetone	25-30
1330-20-7	Xylene	10-15
100-41-4	Ethylbenzene	< 1
74-98-6	Propane	15-20
106-97-8	Butane	15-20
1333-86-4	Carbon Black	< 5

* Listed as known Carcinogen

3. HAZARDOUS IDENTIFICATION

HAZARDOUS POLYMERIZATION: Will Not Occur

ROUTES OF EXPOSURE: Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

INHALATION: Causes irritation of nasal passages and throat. Causes stupor (central nervous system depression).

SKIN CONTACT: Can cause moderate skin injury (reddening and swelling).

EYE CONTACT: Liquid and vapors are irritating to eyes. Can cause severe injury.

INGESTION: Can cause mental sluggishness.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

ACCUTE: Can Cause severe eye irritation, redness, tearing, and blurred vision. Excessive inhalation of vapors can cause nausea, respiratory irritation, central nervous system affects, including dizziness, weakness, fatigue, nausea, headache, and possible unconsciousness and even death. Swallowing can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into lungs can cause chemical pneumonitis, which is fatal.

ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION

MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION.

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.	NIOSH REL	VALUE	UNIT
108-88-3	Toluene	10-15	TWA	50	ppm
78-93-3	Methyl Ethyl Ketone	< 5	TWA	200/590	ppm(mg/m ³)
999-93-3	Hexamethyldisilazane	< 0.5	TWA	0.2	mg/m ³
65996-93-2	Coal Tar Pitch*	< 5	TWA	0.2	mg/m ³
67-64-1	Acetone	25-30	TWA	750	ppm
1330-20-7	Xylene	10-15	TWA	100	ppm
100-41-4	Ethylbenzene	< 1	TWA	100	ppm
74-98-6	Propane	15-20	TWA	1000	ppm
106-97-8	Butane	15-20	TWA	800	ppm
1333-86-4	Carbon Black	< 5	TWA	3.5	mg/m ³

ADDITIONAL ADVICE: Use personal protective equipment, i.e., suitable work clothing, eye goggles and protective gloves. If spraying utilize protective facemask.

9. PHYSICAL PROPERTIES

ODOR: AROMATIC

CHANGE OF STATE	VALUE/AREA	UNIT	METHOD
FREEZING POINT:	N/A	°C	
BOILING POINT:	-17.78 -114.5 (0-238)	°C (°F)	
FLASH POINT:	-17.78 (0) Propellant	°C (°F)	
IGNITION TEMPERATURE:			
SPECIFIC GRAVITY:	0.75	H ₂ O = 1	
% VOLATILE BY VOLUME:	85-95	%	
SOLUBILITY IN WATER:	NEGLIGIBLE		
PH VALUE:	N/A		
VISCOSITY:		CPS	
FLAMMABLE LIMITS:	LEL 1.0 UEL 12.8		
EVAPORATION RATE:	Faster than ether	BUAC = 1	

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Sparks and Open Flame.
MATERIALS TO AVOID: Contact with strong oxidizing, acidic or alkaline agents.
DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.
EYES: Splashes or spray vapors may cause irritation.
SKIN: Substance may be an irritant for sensitive skin.
INHALATION: May cause mild nausea/dizziness in some people when used in confined/unventilated areas. Move patient to fresh air. Give nothing by mouth.
INGESTION: If accidentally swallowed may cause discomfort and requires plenty of water or milk to dilute. Do not induce vomiting. Seek medical assistance.

ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

CHRONIC: Prolonged and repeated skin contact can cause moderate irritation, defatting and dermatitis. Overexposure in laboratory animals has been found the cause of the following affects: Liver abnormalities, kidney damage, lung damage, and spleen damage. Overexposure to this material has been suggested as a cause for liver abnormalities in humans. Prolonged or repeated contact may lead to dermatitis, and with poor hygiene practices, to skin cancer. An Ingredient in this material has been listed as a carcinogen by IARC, NPT, QSHA, and ACGIH.

4. FIRST AID MEASURES

GENERAL ADVICE: Consult Physician immediately
INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Move to an area free from risk of further exposure. Treat symptomatically. Administer oxygen or artificial respiration as needed. **SEEK MEDICAL ATTENTION.**
SKIN CONTACT: Repeated or prolonged contact can cause drying of skin and dermatitis. Remove contaminated clothing and launder thoroughly before reuse. Wash affected skin thoroughly with soap and water. **DO NOT USE SOLVENTS** on skin as they may promote absorption of this material. For severe exposure, get under safety shower after removing clothing, and then **SEEK MEDICAL ATTENTION** if irritation develops or persists after the area has been washed.
EYE CONTACT: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. Refer individual to a physician or ophthalmologist for immediate follow up. **SEEK MEDICAL ATTENTION.**
INGESTION: **DO NOT INDUCE VOMITING.** Give 1-2 cups of milk or water to drink. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEEK MEDICAL ATTENTION.**

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon Dioxide or dry chemical. Use self-contained breathing apparatus if applicable.
EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Stable

SENSITIVITY TO STATIC DISCHARGE: Expected to be sensitive to static discharge when vapors are present between the lower and upper explosive limits.

6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS FOR PERSONNEL: Wear protective clothing. Use self-contained breathing apparatus if required.
ENVIRONMENTAL PRECAUTIONS: Avoid discharge to drains, sewers and natural water supply.
PROCESS FOR CLEANING: Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

7. HANDLING AND STORAGE

HANDLING: Ventilate work area sufficiently. Keep containers closed. Avoid contact with eyes, skin and clothing.
STORAGE: Store between -15°C and +35°C for solvent based coatings and thinners. Ground all metal containers. 55-gallon drums may be stored on their sides in a cradle designed for this purpose.

ROYSTON® DIVISION OF CHASE CORPORATION
MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION

CAS NUMBER	IDENTIFICATION	DERMAL LD50	INHALATION LC50	ORAL LD50
108-88-3	Toluene	12.3 g/kg (rabbit)	4959 ppm (Rat)	7.0 g/kg (Rat)
78-93-3	Methyl Ethyl Ketone	6,480 mg/kg (Rabbit)	23,500 mg/m ³ (Rat)	2,740 mg/kg (Rat)
999-93-3	Hexamethyldisilazane	710 µg/kg (Rat)	8,700 mg/m ³ 4H (Rat)	850 mg/m ³ (Rat)
65996-93-2	Coal Tar Pitch*	N/E	17 mg/m ³ (Rat)	6,200 mg/kg (Rat)
67-64-1	Acetone	9400 g/kg (Guinea Pig)	50,100 mg/M ³ 8H	5,340 mg/M ³ (Rabbit)
1330-20-7	Xylene	12.2g/kg (Rabbit)	4,550 ppm (Rat)	4.3g/kg (Rat)
100-41-4	Ethylbenzene	15.4 g/kg (Rabbit)	2,824 mg/m ³ (Rat)	3.5 mg/kg (Rat)
74-98-6	Propane	N/E	N/E	N/E
106-97-8	Butane	N/E	N/E	N/E
1333-86-4	Carbon Black	N/E	27,000 mg/M ³ (Rat)	> 8,000 mg/kg (Rat)

CAS NUMBER	IDENTIFICATION	CARCINOGENICITY ACGIH	IARC	TERATOGENICITY	MUTAGENICITY
108-88-3	Toluene	N/E	N/E	Yes	N/E
78-93-3	Methyl Ethyl Ketone	N/E	N/E	N/E	N/E
999-93-3	Hexamethyldisilazane	N/E	N/E	N/E	N/E
65996-93-2	Coal Tar Pitch*	Yes	Yes 2 B	N/E	Yes
67-64-1	Acetone	N/E	N/E	N/E	N/E
1330-20-7	Xylene	N/E	N/E	N/E	N/E
100-41-4	Ethylbenzene	Yes	Yes 2 B	N/E	N/E
74-98-6	Propane	N/E	N/E	N/E	N/E
106-97-8	Butane	N/E	N/E	N/E	N/E
1333-86-4	Carbon Black	Yes	Yes 2 B	Yes	N/E

VOLATILE ORGANIC COMPOUNDS: 12. ECOLOGICAL INFORMATION
624 Grams Per Liter (g/l), 5.29 Pounds Per Gallon (lb/g).

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

SHIPPING	AIR	OCEAN	TRUCK
Proper Shipping Name	AEROSOLS, FLAMMABLE	AEROSOLS	CONSUMER COMMODITY
Hazardous Code			
UN Number	UN 1950	UN 1950	None
IMDG Page:		2102, LTD QTY 910	
Outer Packaging	16 KG	STRONG INDUSTRIAL PACKAGING	STRONG INDUSTRIAL PACKAGING
Markings			MARK ON PACKAGE
Label	FLAMMABLE GAS	NO LABEL	OMR-D NO LABEL